

Twin Spijlen

Het verminderen van de doorval

		BESCHIKBARE STEEK (+ DOORVAL)									
SPIJL DIAMETER + MATERIAAL		28 /14	32/16	35/17	36/18	40/20	42/21	44/22	45/22	50/25	56/28
Ø 5	RVS		(11)			(15)	(16)			(20)	(23)
	Klasse C / B	(9)	(11)	(12)	(13)	(15)	(16)			(20)	
Ø 6	RVS	(8)	(10)	(11)	(12)	(14)		(16)	(16)		
	Glasfiber	(8)	(10)	(11)	(12)	(14)	(15)	(16)	(16)	(19)	
	Glasfiber gecoat	(8)	(10)	(11)	(12)	(14)	(15)	(16)	(16)	(19)	
	Klasse C/ B	(8)	(10)	(11)	(12)	(14)	(15)	(16)	(16)	(19)	
Ø 7	RVS	(7)	(9)		(11)	(13)	(14)			(18)	
	Klasse C	(7)	(9)	(10)	(11)	(13)	(14)	(15)	(15)	(18)	(21)
Ø 8	RVS	(6)		(9)	(10)	(12)	(13)	(14)		(17)	(20)
	Glasfiber	(6)	(8)	(9)	(10)	(12)	(13)	(14)	(14)	(17)	(20)
	Klasse C	(6)	(8)	(9)	(10)	(12)	(13)	(14)	(14)	(17)	(20)
Ø 9	RVS		(7)			(11)				(16)	(19)
	Klasse C			(8)	(9)	(11)				(16)	(19)
Ø 10	RVS		(6)	(7)	(8)	(10)		(12)	(12)	(15)	(18)
	Glasfiber		(6)	(7)	(8)	(10)		(12)	(12)	(15)	(18)
	Glasfiber gecoat		(6)	(7)	(8)	(10)		(12)	(12)	(15)	(18)
	Klasse C		(6)	(7)	(8)	(10)		(12)	(12)	(15)	(18)
	GELASTE TWIN SPIJL BORON (A or B)		(6)	(7)	(8)	(9)	(10)	(12)	(12)	(15)	



BESCHIKBAAR /
VOORRAAD